PANORAMA PRO 501 @ s



Rated for use as a ground flood or a wall mounted security flood, with COB technology for greater efficacy.

Performance


- High output COB LED produces up to 3800 lumens using only 50 watts, saving 67% over 150 watt halogen floods
- Long life LED saves in labor costs by reducing lamp replacements
- IP65 rated housing has attached yoke with 180° tilt and durable powder coat finish for great resistance to the elements

Construction

- Die-cast aluminum body with internal 120-277V driver and 16" 3-conductor 18AWG SJTW 'whip'
- COB LED has aluminum reflector to boost light output and create a wide beam of even light distribution
- COB and reflector are protected by gasket lined tempered glass lens cover which is sealed to frame

Installation

- Canopy kit includes 1/2" NPS threaded hole for use with pencil photocell and/or for use with 4" round watertight junction box (order each separately)
- Fixture can be mounted to structural part of building or to concrete pad located at ground level using attached yoke, then 'whip' routed to watertight junction box located nearby (within ± 12")
- Loosen 10mm bolts at side of yoke to set tilt, then retighten to secure



*Footcandle values based on 10ft mounting height.

Specifications

Series	Panorama PRO 501
Input voltage	100-277V, 50/60Hz AC
Color temperature	3000K / 4500K
CRI	75+
Wattage	50W
Lumens	3500Lm / 3800Lm
Beam angle	106° (180° tilt)
Housing	Die-cast coated aluminum
Lens	Tempered glass
Rating	c/UL/us Listed for wet locations
Dimensions	11-1/4"W x 9-1/8"H x 5-5/8"D
Switching	Branch circuit or photocell*
Mounting	Yoke, canopy or watertight j-box
LED type	COB (Chip on Board) LED
Rated life	50,000 hrs

Panorama Pro 501 & Accessories



FL-501-30-DB (Dark Bronze) FL-501-30-WH (White) Panorama Pro 501 3000K / 50W / 3500Lm



FL-501-45-DB (Dark Bronze) FL-501-45-WH (White) Panorama Pro 501 4500K / 50W / 3800Lm



C-501-DB (Dark Bronze) C-501-WH (White) Canopy Mount for FL-501 *Includes 1/2" NPS for photocell



PC-120 (120V AC) PC-277 (208-277V AC) Dusk to dawn pencil photocell (requires C-501)